

QUESTED HQ210

Mid-Field/Main System Passive Reference Monitor



The HQ210 is the largest passive monitor built by Quested and offers a truly neutral response at high levels.

With its rotatable Mid/HF section, it can be used vertically or horizontally, soffit-mounted as a main monitor or used mid-field on a stand.

The three sections of the audiophile quality, passive filter networks are independently accessible on the triple pair binding post tray making triwiring, or tri-amping possible.

There are also upgrade paths that could ultimately convert the HQ210 into the Active Q210.

Typical applications: Main monitor in mid sized control rooms, L/C/R system with VH Sries as surrounds, or initial monitor when a later Active upgrade is anticipated.

We recommend a Quested AP1300 amplifier for use with the HQ210.

Size (WxHxD)	485(w) x 612(h) x 324(d) mm
Weight	38 kgs
Drivers	Bass: 2 x 250 mm (10") cone Mid: 1 x 75mm (3") soft dome HF: 1 x 28mm (1.125") soft dome
Maximum SPL	115dB(C)
Sensitivity	92dB at 1 watt at 1 meter
Frequency Response	45Hz - 20kHz +/-2 dB
Input Connectors	Triple pair gold plated binding posts accepts 4mm banana plugs or bare wire
Nominal Impedance	8 ohms
Crossovers	Low/Mid - 90Hz, Mid/High - 2.8 kHz
Power requirements	Amplifier rated at 300 -900 watts RMS at 8 Ohms

Quested Monitoring Systems

Unit 8, Kingsgate, Heathpark, Honiton, Devon EX14 1YG, UK - T +44 (0)1404 41500 - E info@quested.com

www.quested.com



EAT



SLEEP



MIX